

Metal Fiber Terminal Box

Quick Details

Place of Origin: Shenzhen, China (Mainland);
Brand Name: OPTICO;
Max Ratio: 1:16;
Material: steel;
Installation method: wall-mounted or pole mount;
Max Capacity(F): 16 fiber;
Type: Outdoor/Indoor;
Working Temperature: -40+80℃;
Certification: RoHs ,ISO 9001;
Packaging Details: 1pc/inner box, suitable quantity per outer cartons;
Delivery Time: 10~20 days after deposit;



Metal Fiber Terminal Box

Product Description:

This 16 ports fiber optical terminal box terminates up to 2 fiber optic cables, offers spaces for splitters and up to 8 fusions, allocates up to 16 SC adapters and working under both indoor and outdoor environments. It is a perfect cost-effective solution-provider in the FTTx networks.

Descriptions:

metal material used ensures the body strong and light;
Easy installations: Ready for wall mount – installation kits provided;
Ready for splitters: designed space for adding splitters;
Space saving! Double-layer design for easier installation and maintenances;
Lower layer for splitters and over length fiber storage;
Upper layer for splicing, cross-connecting and fiber distribution;
Cable fixing units provided for fixing the outdoor optical cable;
Protection Level: IP65;
Accommodates both cable glands as well as tie-wraps;
Accommodates splitters and up to 16SC simplex adapters;
Max allowance for entry cables: max diameter 16mm, up to 2 cables;

Max allowance for exit cables: up to 16 simplex cables;

Operation conditions:

Temperatures:-40°C -- 60°C;

Humidity:93% at 40°C ; ;

Air Pressure:62kPa – 101kPa;

Package includes:

Terminal box, 1 unit;

Wall mount installation accessories, 1 set;

Company Pictures:

